



Rack Mount LIU, 19 inch –Configurable to 12 /24/48 Duplex Ports or 24/48/96/120 Simplex Ports - Single Mode ,Multi-Mode and MPO



Specification :

1. Height : 1U(43.65mm) Width : 19"(482.6mm) Depth : 10"
2. Shelf Mounting Adjustment Range : 0~245.0mm
3. Material : SPCC, 1.2mm Thickness, BK(RAL9005)
4. Operating Temperature : -20°C to +70°C
5. Net Weight : 2.8kg.

Drawing Ref: 1 U Size, 19 " Rack Mount, Options: 12/24/48/120 SX Ports SM / MM/MPO



HD cassette with MPO 24 core to 24 LC , Simplex , SMF/ MMF Options, Totally 5 Cassettes can be installed in the 1 U Size, 19 Inch LIU with 120 core fiber connections. Ideal suited for Data Center and compact area, where ever space constrains are there.

- Easy to Use ,Quick to Install, Factory Made – No Field Splicing ,Customizable and Re-usable modules.
- Flexibility to switch the front plate so that quick reconfigurations and re use the LIU's.
- MPO 24 Core Trunk Cable with Type A or Type B can be used to connect two LIU's.
- Applications: Extension of 10G/40G/100G/400G Links, and Rack to Rack Harness cabling.



Typical Application: Server Port → 40G/100G MPO cable → HD LIU with Cassette → 40G/100G MPO cable → Switch /Storage Port 40G/100G
 Server Port → 10G/25 G Harness Cable → HD LIU with Cassette → 10G/25 G Harness Cable → Switch port 10G/25G
 Server Port → 40G/100G MPO cable → HD LIU with Cassette → MPO to LC Breakout Harness cable → Switch /Storage Ports 10G/25 G

SM Fiber – Data Center and Cloud Connect Solutions WWW.SMVADD.COM , smvadd@gmail.com , 9886607135

